

QDBPC50E Construction Connector System

The revolutionary screw connector attachment, QDBPC50E, for installing Simpson Strong-Tie® CE-labelled CSA connector screws. By using QDBPC50E you will achieve a significant time saving of at least 50% due to the fact that no time is wasted on searching for loose screws in a box, installing them with a screwdriver and starting the process all over again. When using the new attachment, a new screw is ready as soon as the first has been installed. There is no waiting or lost screws by using this system.



QDBPC50E Attachment

- Part of the Quik drive range.
- Use with CSA collated screws to install connectors such as angle brackets and joist hangers to timber.
- Suitable for screws 35mm to 50mm long.
- Use with Mandrel code: MANDREL 128E.
- Connects easily with screw gun or Quik drive extension.
- Teflon coated moving parts for a long life.

QDBPC50E includes	Model No.	Compatible Screws
Attachment	QDBPC50E	CSA
Mandrel	MANDREL 128E	
Spare Bits	BITLTX20E (x1)	



The CSA connector screw is specifically designed to fasten steel brackets to wood. The smooth shaft under the head fits tightly to the hole in the bracket. This provides a stiff connection with larger cross-resistance than standard screws. Fibre cut tip allows for easy and fast driving. In most load bearing capacity tables for brackets, CNA connector nails are listed as fasteners.

CSA screws can replace CNA nails, when used in the same connection detail, as they have greater pullout strength per unit than a CNA nail, and at least the same cross-bearing capacity.

Minimum requirements for spacing and minimum edge and end distances for connector screws CSA5,0xℓ are the same as for connector nails CNA4,0xℓ.

Model No.	Length [mm]	Diameter	Qty per Strip	Material	Application	Qty per Pack
CSA5.0X40T	40	5.0	25	Carbon Steel	For fastening connectors to wood.	1,500

