

Deck-Drive™

DHSD HARDWOOD TX Screw

SIMPSON
Strong-Tie®



Look for the yellow strip. Your guarantee of quality and performance from **Genuine Quik Drive® Fasteners**.

Available loose for hand-drive and collated for Quik Drive

The DHSD is specially designed to penetrate the hardest timber decking products with ease. Its unique drill point virtually eliminates countersinking and splitting without pre-drilling. The DHSD is suitable for fixing decking to both hardwood and softwood joists.

Features and Benefits

- No pre-drilling required in most hardwood
- Raised countersinking head delivers a professional and decorative finish
- Unique ribbed shank provides greater strength and holding power
- Low torque design for easy driving
- Design virtually eliminates splitting of hardwood decking
- Stainless Steel has the ductility to allow for movement of timber decking
- 6-lobe drive helps prevent driver-bit cam-out, resulting in easier driving and beautiful looking finish
- Type 316 grade Stainless Steel for highly corrosive environments

Applications

- For hardwood and softwood decking in residential or commercial applications
- Decking on board walks in highly corrosive environments
- Exterior cladding or paneling for patio privacy screens
- Certain exterior fascia board applications

Material

- 316 Stainless Steel (T20 6-Lobe Drive product only)



Raised compact head
for a decorative finish



Ribbed shank
provides greater holding power



Hardwood drill point
virtually eliminates splitting and the need for pre-drilling



Note: Pre-drilling may be required on weathered boards or when drilling close to the edge

Deck-Drive™

DHSD HARDWOOD TX Screw



Collated for Quik Drive®


- Coarse threads
- Hardwood drill point
- 316 Stainless Steel
- T-20 6-lobe drive

Corrosion Resistance Level
SEVERE



Compatible Tool: PRO250, PRO300
Bit(s) included with every box of screws.

PRO250 is the preferred Quik Drive® attachment when used in conjunction with the decking nose clip (PDECKNC-RC).



Dia.	Length	Model No.	Replacement Bit	Barcode	Box Qty	Dimensions (WxLxH)	Weight
12 g	50 mm	SSDHSD50TSA	BITTX20-RC10	707392010203	1000	273 x 365 x 124 mm	5.67kg
12 g	65 mm	SSDHSD65TSA	BITTX20-RC10	707392010210	1000	273 x 365 x 124 mm	6.65kg

Loose for Hand Drive

- Coarse threads
- Hardwood drill point
- 316 Stainless Steel
- T-20 6-lobe drive



Corrosion Resistance Level
SEVERE



Bit(s) included with every box of screws

Dia.	Length	Model No.	Replacement Bit	Barcode	Box Qty	Box/ Ctn	Box Dimension (WxLxH)	Ctn Dimension (WxLxH)	Pack Weight
12 g	50 mm	SSDHSD50TR250		707392007739	250	6	95 x 187 x 78mm		1.32kg
		SSDHSD50TR1100		707392010197	1100	1	210 x 165 x 175mm		5.54kg
			BIT20T-2-R2					160 x 350 x 245mm	
12 g	65 mm	SSDHSD65TR250		707392007753	250	6	95 x 187 x 78mm		1.57kg
		SSDHSD65TR1100		707392007760	1100	1	210 x 165 x 175mm		6.61kg