

Date: August 2023

Product Disclosure Information – Company Assessment

Product Name: PDKIT, PKADJ Patio Deck Kits – Deck Structure Building Products

Product Category: Connectors

Product Identifier: UPC (Unique Product Code)

PDKIT - 707392025252

PKADJ - 707392025276

1.

Product Description

The PDK product consists of an engineered extruded aluminium joist and nylon base clips, providing a fixed height of 35mm top of aluminium joist height

The PKADJ Patio Deck Kit Height Adjuster is an optional extra – this product allows the PDK assembly to be adjusted in small increments to a maximum top of joist height of 65mm. It is made from engineered nylon.

2.

Relevant Building Code Clauses

Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

Clause B2 DURABILITY: Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

3.

Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website (strongtie.co.nz) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.

4.

Scope of use:

Designed for those areas where there is an extremely minimal step-down from the house or apartment block to your patio area, this product consists of an engineered extruded aluminium joist and nylon base clips, providing a fixed height of 35mm (1 3/8 inches) top of aluminium joist height. – meaning that a typical decking board arrangement can still be installed at less than 60mm (2 1/4 inches) over your concrete slab or tiled area.

5.**Conditions of Use****Installation Information: Installation Skill Level Requirements**

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

6.**Maintenance**

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance tables. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website (www.strongtie.co.nz) or by following this link.

<https://strongtie.co.nz/resources#corrosion-information>

7.**Supporting Documentation**

Type: Product Flyer & Technical Data Sheet

Version: Original KlevaKlip Literature

Web: <https://klevaklip.com.au/Patio-Deck-Kit>

8.**Company Contact Details**

Importing Branch:	Simpson Strong-Tie New Zealand
Address:	52A Arrenway Drive Albany, Auckland 0632 New Zealand
Phone:	+64 9 477 4440
Website:	www.strongtie.co.nz

Manufacturing Branch:	Sourcing Branch 8300 China
Address:	Zhangjiagang, 215600 Jiangsu Province, P.R. China
Phone:	
Website:	www.simpsonmfg.com
Phone:	Please call NZ Head Office.

9.**Warnings and Bans**

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?
No

10.**Safety:****F2 Hazardous building materials****F2.3.1**

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

11.

Appendix – BPIR Ready Selections

B1 Structure

B1.3.1

Buildings, building elements and site work shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings; building elements and site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (g) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage

B1.3.4

Due allowances shall be made for:

- the consequences of failure,
- the intended use of the *building*,
- effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of *buildings*

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (a) The life of the building, being not less than 50 years, if:
 - those *building elements* (including floors, walls, and fixings) provide structural stability to the *building*, or
 - those *building elements* are difficult to access or replace, or
 - failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the building