

Date: August 2023

Product Disclosure Information – Company Assesment

Product Name: Quik Drive Adaptors **Product Category**: Tools/Accessories

Product Identifier: UPC (Unique Product Code)

DWAG2 - 746056019985 DWA3G2 - 746056546825 HIAG2 - 746056022893 MAAG2 - 746056019992 MAA3G2 - 746056665205 MIAG2 - 746056019879

1.

Product Description

Aluminium Fitting designed to fit Makita or DeWALT drill drivers to enable the Quik Drive® Auto-Feed Screw Driving System to be safely and securely connected.

2

Relevant Building Building Code Clauses Code Clauses

Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

Clause B2 DURABILITY: Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

3.

Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website (strongtie.co.nz) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.



Scope of use:

Used to connect the Quik Drive Auto-Feed Screw Driving System to different brands of screw driver guns, generally those with a built in clutch mechanism.

Conditions of Use

Installation Information: Installation Skill Level Requirements

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

Maintenance

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website (www.strongtie.co.nz) or by following this link. https://strongtie.co.nz/resources#corrosion-information

Supporting Documentation

Type: New Zealand Price Book Version: P-SSTNZ23 © 2023

Type: Anchoring and Fastening Catalogue

Version: C-AF-AUNZ18

Web: https://strongtie.co.nz/products/quik-drive-auto-feed-screw-driving-systems

Company Contact Details

Importing Branch: Simpson Strong-Tie New Zealand

Address: 52A Arrenway Drive

Albany, Auckland 0632 New

Zealand

Phone: +64 9 477 4440 Website:

www.strongtie.co.nz

Manufacturing Branch: ST Souring Office Taiwan

Room A7, 24F, No.260 Address:

> Zhongshan 2nd Road Qianzhen District Kaohsiung City 806

Website: www.simpsonmfg.com Please call NZ Head Office. Phone:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No



10.

Safety:

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

11.

Appendix – BPIR Ready Selections

B1 Structure

B1.3.1

Buildings, building elements and site work shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during construction or alteration and throughout their lives.

B1.3.2

Buildings, *building elements* and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*; *building elements* and *site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (q) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage

B1.3.4

Due allowances shall be made for:

- the consequences of failure,
- the intended use of the building,
- effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of buildings



10.

Appendix - BPIR Ready Selections

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (a) The life of the building, being not less than 50 years, if:
 - those building elements (including floors, walls, and fixings) provide structural stability to the building, or
 - those *building elements* are difficult to access or replace, or
 - failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the building