Date: August 2023

Product Disclosure Information – Company Assesment

Product Name: SDWS16 Framing Screws Product Category: Structural Fasteners Product Identifier: UPC (Unique Product Code)

SDWS16312QR50

707392010395

Product Description

The SDWS16 Framing Screw is a structural fastener 4.0mm x 89mm designed for replacing nails in general framing applications. Ribbed Washer Head Saw Tooth Point Double Barrier Coating T25-6 Lobe SST have also approved these screws for use in roof batten or rod purlin application.

2.

1.

Relevant Building Building Code Clauses Code Clauses

Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

Clause B2 DURABILITY: Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website (strongtie.co.nz) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.



Scope of use:

The SDWS16 Framing Screw is suitable for replacing nails in many framing applications where you are wanting a more secure and precise connection, especially if you require greater holding power and pullout resistance, it can also be easily removed if required. Approved for use in roof batten and purlin application.

Conditions of Use

Installation Information: Installation Skill Level Requirements

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

Maintenance

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website (<u>www.strongtie.co.nz</u>) or by following this link. <u>https://strongtie.co.nz/resources#corrosion-information</u>

7.

Supporting Documentation

Type: Product Flyer

Version: F-F-SDWS-SDWH-AUNZ22 4/ 22

Type: Technical Data Sheet – General Framing Version: TDS-SDWS-AUNZ22

Type: Technical Data Sheet – Roof Batten and Purlin Application Version: TDS-SDWS-NZ23-RB

Web: https://strongtie.co.nz/products/sdws-sdwh-framing-screws

8.

Company Contact Details

Importing Branch: Address:	Simpson Strong-Tie New Zealand 52A Arrenway Drive Albany, Auckland 0632 New Zealand	Manufacturing Branch: Address:	SST Souring Office Taiwan Room A7, 24F, No.260 Zhongshan 2nd Road Qianzhen District
Phone: Website:	+64 9 477 4440 www.strongtie.co.nz	Website: Phone:	Kaohsiung City 806 www.strongtie.co.nz Please call NZ Head Office



9. Warnings and Bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

10. Safety:

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

11.

Appendix – BPIR Ready Selections

B1 Structure

B1.3.1

Buildings, building elements and *site work* shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*; *building elements* and *site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (g) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage

11.

Appendix – BPIR Ready Selections

B1.3.4

Due allowances shall be made for:

- the consequences of failure,
- the intended use of the *building*,
- effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of buildings

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

(a) The life of the building, being not less than 50 years, if:

- those building elements (including floors, walls, and fixings) provide structural stability to the building, or
- those *building elements* are difficult to access or replace, or
- failure of those building elements to comply with the building code would go undetected during both normal use and maintenance of the building