

#### Date: August 2023

Product Disclosure Information – Company Assesment

Product Name: BFHSD Bi-Metal Screw Product Category: Fasteners Product Identifier: UPC (Unique Product Code)

BFHSD BI-METAL Screw SSBFHSD2R250 - 707392426738 SSBFHSD2R40 - 707392010227

# Product Description

Timber to Steel 316 Grade Stainless Steel Screw Gauge: 10G Length: 50mm Ribbed Flat Head # Square Drive

### 2.

Relevant Building Building Code Clauses Code Clauses

### Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

**Clause B1 STRUCTURE:** Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

**Clause B2 DURABILITY:** Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

**Clause E2 EXTERNAL MOISTURE:** Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

**Clause F2 HAZARDOUS BUILDING MATERIALS:** Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

# 3.

### Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website (strongtie.co.nz) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.



# Scope of use:

The BFHSD Bi-Metal screw is designed for Timber-to-Steel joist (1.2mm–2.4mm-steel thickness) applications. The winged design cuts a clearance hole and avoids sheet ride. The Bi-Metal design consists of 316 Stainless Steel and a Carbon Steel tip, which is perfect for steel joist applications without compromising on corrosion resistance.

#### 5. Conditions of Use

### Installation Information: Installation Skill Level Requirements

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

### 6.

### Maintenance

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website (<u>www.strongtie.co.nz</u>) or by following this link. <u>https://strongtie.co.nz/resources#corrosion-information</u>

## 7.

Supporting Documentation

Type: Deck Drive Premium Fasteners Brochure Version: S-F- DD – NZ23 Web: <u>https://strongtie.co.nz/products/bfhsd-bi-metal-screw-timber-steel-collated-loose</u>

#### 8. Company Contact Details

Importing Branch: Address:	Simpson Strong-Tie New Zealand 52A Arrenway Drive
	Albany, Auckland 0632 New
	Zealand
Phone:	+64 9 477 4440
Website:	www.strongtie.co.nz

Manufacturing Branch:	SST Branch 8200 Taiwan
Address:	Room A7, 24F, No.260
	Zhongshan 2nd Road
	Qianzhen District
	Kaohsiung City 806
Website:	www.simpsonmfg.com
Phone:	Please call NZ Head Office.

#### 9. Warnings and Bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No



#### 10. Safety:

## F2 Hazardous building materials

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

## 11.

Appendix – BPIR Ready Selections

## **B1 Structure**

## B1.3.1

*Buildings, building elements* and *site work* shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

## B1.3.2

*Buildings, building elements* and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

## B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*; *building elements* and *site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (g) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage

## B1.3.4

## Due allowances shall be made for:

- the consequences of failure,
- the intended use of the *building*,
- effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of *buildings*



# 11.

### Appendix – BPIR Ready Selections

### **B2** Durability

## B2.3.1

*Building elements* must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

(a) The life of the building, being not less than 50 years, if:

- those building elements (including floors, walls, and fixings) provide structural stability to the building, or
- those *building elements* are difficult to access or replace, or
- failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the building