

Date: August 2023

Product Disclosure Information – Company Assesment

Product Name: SSDSD, SSDHSD, SSDHW - Collated for Quik Drive

Product Category: Deck Drive Premium Fasteners Product Identifier: UPC (Unique Product Code)

<u>DSD HARDWOOD Screw</u> SSDSD50SA - 707392007678 SSDSD65SA - 707392007647 <u>DHSD HARDWOOD Screw</u> SSDHSD50TSA - 746056696902 SSDHSD60TSA - 746056675808 <u>DHW HARDWOOD Screw</u> SSDHW60SA - 707392450443

1.

Product Description

Collated Deck Drive Stainless Steel Decking Screws 10G – 14G x 50mm – 100mm 300 Grade Stainless Steel (305 -316 Grade Stainless Steel)

Designed to use with the Quik Drive Tool and Deck Clip Attachment

2.

Relevant Building Building Code Clauses Code Clauses

Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

Clause B2 DURABILITY: Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

3.

Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website (strongtie.co.nz) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.



Scope of use:

The SSDSD, SSDHSD, and SSDHW Hardwood-to-Hardwood screws are ideal for hardwood decking applications and is specifically designed to penetrate the hardest timber with ease. The unique Drill Point virtually eliminates splitting without the need of pre-drilling. The screws have different types of heads (Flat Decorative, Raised countersunk, and Compact depending on what finish or look the homeowner or builder wants they all deliver a professional finish for a decorative style deck.

Conditions of Use

Installation Information: Installation Skill Level Requirements

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

Maintenance

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website (www.strongtie.co.nz) or by following this link. https://strongtie.co.nz/resources#corrosion-information

Supporting Documentation

Type: Deck Drive Premium Fasteners Brochure

Version: S-F- DD - NZ23

Web: https://strongtie.co.nz/products/dsd-hardwood-decking-screw-collated-loose Web: https://strongtie.co.nz/products/dhsd-hardwood-decking-screw-collated-loose Web: https://strongtie.co.nz/products/dhsd-hardwood-decking-screw-collated-loose

Company Contact Details

Importing Branch: Simpson Strong-Tie New Zealand

Address: 52A Arrenway Drive

Albany, Auckland 0632 New

Zealand

Phone: +64 9 477 4440 Website: www.strongtie.co.nz Manufacturing Branch: SST Souring Office Taiwan

Address: Room A7, 24F, No.260

> Zhongshan 2nd Road Qianzhen District Kaohsiung City 806

Website: www.simpsonmfg.com Phone: Please call NZ Head Office.



9.

Warnings and Bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

10.

Safety:

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

11

Appendix – BPIR Ready Selections

B1 Structure

B1.3.1

Buildings, building elements and site work shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during construction or alteration and throughout their lives.

B1.3.2

Buildings, *building elements* and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*; *building elements* and *site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (g) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage



11.

Appendix – BPIR Ready Selections

B1.3.4

Due allowances shall be made for:

- the consequences of failure,
- the intended use of the building,
- effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of buildings

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (a) The life of the building, being not less than 50 years, if:
 - those building elements (including floors, walls, and fixings) provide structural stability to the building, or
 - those building elements are difficult to access or replace, or
 - failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the building