

Date: August 2023

## Product Disclosure Information – Company Assessment

**Product Name:** SSDTH, SSWSC, SS3D Stainless Steel Wood Screws – Collated for Quik Drive  
**Product Category:** Fasteners  
**Product Identifier:** UPC (Unique Product Code)

### Stainless Steel – Timber Screws

SSDTH2SA - 746056564393  
SSDTH212S - 746056055167  
SSDTH3S - 746056057697  
SSWSC134BS - 707392864707  
SSWSC2BSA10 - 746056001409  
SS3DSC212BS - 746056037897  
SS3DSC3BS - 746056037934  
SS3DSC212BS316 - 746056258506  
SS3DSC3BS316 - 746056369608

1.

## Product Description

### SSDTH:

Gauge: 7G  
Length: 50mm - 75mm  
Finish: 305 Stainless Steel

### SSWSC:

Gauge: 8G – 10G  
Length: 45 - 50mm  
Finish: 305 Stainless Steel

### SS3D:

Gauge: 10G  
Length: 65mm - 75mm  
Finish: 305 and 316 Stainless Steel

2.

## Relevant Building Code Clauses

Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

**Clause B1 STRUCTURE:** Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

**Clause B2 DURABILITY:** Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

**Clause E2 EXTERNAL MOISTURE:** Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

**Clause F2 HAZARDOUS BUILDING MATERIALS:** Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

3.

## Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website ([strongtie.co.nz](http://strongtie.co.nz)) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.

4.

## Scope of use:

**SSDTH:** Simpson Strong-Tie Stainless Steel Trim Head screws are ideal fasteners for many exterior timber applications, including weatherboards, decking, window and door facings, boxed corners and even aluminium window and door jambs.

**SSWSC:**

The SSWSC timber screw is ideal for timber-to-timber applications with its Coarse Thread and Flat Head with Nibs. The Flat Head with Nibs design allows for easy countersinking for a clean flush finish.

**SS3D:** The SSDSC screw is perfect for timber-to-timber applications where 65mm or 75mm Stainless Steel fasteners are required. The Bugle Head provides a clean countersunk finish whilst the Type-17 Point is perfect for timber-to-timber decking, sheet flooring or flat ply wood roofing applications.

5.

## Conditions of Use

### Installation Information: Installation Skill Level Requirements

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

6.

## Maintenance

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website ([www.strongtie.co.nz](http://www.strongtie.co.nz)) or by following this link.

<https://strongtie.co.nz/resources#corrosion-information>

7.

## Supporting Documentation

**Type: Product Flyer**

**Version: F-F-THETSNZ21 (SSDTH)**

**Type: Anchor and Fastening Catalogue/Product Flyer**

**Version: C-AF-AUNZ18 page 197 (SSWSC)**

**Type: Anchor and Fastening Catalogue/Product Flyer**

**Version: C-AF-AUNZ18 page 209 (SS3D)**

**Web:** <https://strongtie.co.nz/products/trim-head-exterior-timber-screw-collated-loose>

**Web:** <https://strongtie.co.nz/products/wsc-timber-screw-flooring-screw-collated>

**Web:** <https://strongtie.co.nz/products/ss3dsc-timber-screw-flooring-collated>

**Branz: SSDTH:**

<https://www.branz.co.nz/appraisal-codemark-certificates/1044-2019-simpson-strong-tie-weatherboard-screws/>

8.

## Company Contact Details

**Importing Branch:** Simpson Strong-Tie New Zealand  
**Address:** 52A Arrenway Drive  
Albany, Auckland 0632 New Zealand  
**Phone:** +64 9 477 4440  
**Website:** [www.strongtie.co.nz](http://www.strongtie.co.nz)

**Manufacturing Branch:** SST Sourcing Office Taiwan  
**Address:** Room A7, 24F, No.260  
Zhongshan 2nd Road  
Qianzhen District  
Kaohsiung City 806  
**Website:** [www.simpsonmfg.com](http://www.simpsonmfg.com)  
**Phone:** Please call NZ Head Office.

9.

## Warnings and Bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

10.

## Safety:

### F2 Hazardous building materials

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

11.

## Appendix – BPIR Ready Selections

## B1 Structure

### B1.3.1

*Buildings, building elements* and *site work* shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

### B1.3.2

*Buildings, building elements* and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

### B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings; building elements* and *site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (g) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage

### B1.3.4

Due allowances shall be made for:

- the consequences of failure,
- the intended use of the *building*,
- effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of *buildings*

## B2 Durability

### B2.3.1

*Building elements* must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (a) The life of the building, being not less than 50 years, if:
  - those *building elements* (including floors, walls, and fixings) provide structural stability to the *building*, or
  - those *building elements* are difficult to access or replace, or
  - failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the building