

Date: August 2023

Product Disclosure Information – Company Assessment

Product Name: WSC, WSV, WSNTL Flooring Screws – Collated for Quik Drive

Product Category: Fasteners

Product Identifier: UPC (Unique Product Code)

Flooring Screws Twin Lead and Timber Screws

WSC114SA - 746056423157

WSV45SA - 707392014126

WSV50SA - 707392004622

WSV64SA - 707392014133

WSV75SA - 707392014140

WSNTLG2SA - 746056421115

1.

Product Description

WSC: 8G x 32mm Zinc Flooring or Overlay Screw

WSV: 10G x 45mm – 75mm Zinc Flooring Screw

WSNTLG: 8G x 50mm Class 3 Galvanised Flooring Screw

2.

Relevant Building Code Clauses

Simpson Strong-Tie products,

If designed, installed, and maintained in accordance with 3603 and 3604, meet the following provisions of the NZBC.

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Simpson Strong-Tie products meet these requirements for loads arising from self-weight, wind and impact [i.e. B1.3.3(a), (h) and (j)]. See Paragraphs 8.1 to 8.3.

Clause B2 DURABILITY: Performance B2.3.1 (b), 15 years and B2.3.2. Simpson Strong-Tie Products meet these requirements. See Paragraphs 9.1 to 9.3.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.2. Simpson Strong-Tie Stainless Steel products meet this requirement. See Paragraph 10.1.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. Simpson Strong-Tie meet this requirement and will not present a health hazard to people.

3.

Contributions to Compliance

Refer to Simpson Strong-Tie (New Zealand) Limited Website (strongtie.co.nz) for details of the current technical literature for all Simpson Strong-Tie products. The Technical Literature must be read in conjunction with all aspects of design, use, installation and maintenance contained in the technical literature and within the scope of appropriate design, application and installation as per the relevant building code clauses within the current New Zealand Building Code. If certain products have been Branz Appraised, the appraisal will be found under the technical documents tab on the product information page or the relevant product.

4.

Scope of use:

WSC: The WSC timber screw is ideal for timber to timber applications with its Coarse Thread and Flat Head with Nibs. The Flat Head with Nibs design allows for easy countersinking for a clean flush finish. Suitable for overlay flooring.

WSV: The WSV is the best solution for fixing subfloor, bracing, bottom plate and stair applications. Simpson Strong-Tie has re-engineered its popular subfloor screw to reduce torque and save time. The WSV screw reduces the gaps between the joist and subfloor that cause floor squeaks due to its superior holding power.

WSNTLG: The galvanised WSNTLG timber screw is ideal for fastening subfloor, cladding, sill plates, stair treads and general exterior timber-to-timber applications using the Quik Drive® auto-feed screw driving system. The holding power of WSNTLG screws reduces the gaps between the joist and subfloor that cause floor squeaks.

5.

Conditions of Use

Installation Information: Installation Skill Level Requirements

Installation of Simpson Strong-Tie products must be completed by, or under the supervision of a qualified Licensed Building Practitioner. Installation instructions can be found on the Simpson Strong-Tie website, within applicable and appropriate literature associated with the relevant product.

6.

Maintenance

Simpson Strong-Tie structural elements do not require regular maintenance as long as they are selected using our corrosion guidance. In exposed conditions, regular inspection of fixings and fasteners should be conducted. Corrosion information can be found on the website (www.strongtie.co.nz) or by following this link.
<https://strongtie.co.nz/resources#corrosion-information>

7.

Supporting Documentation

Type: Product Flyer

Version: C-AF-AUNZ18 page 197 (WSC Zinc)

Type: Product Flyer

Version: F-F-WSV-NZ19 (WSV)

Type: Anchor and Fastening Catalogue/Product Flyer

Version: C-AF-AUNZ18 page 196 (WSNTLG)

Web: <https://strongtie.co.nz/products/wsc-timber-screw-flooring-screw-collated>

Web: <https://strongtie.co.nz/products/wsv-timber-screw-flooring-screw-collated>

Web: <https://strongtie.co.nz/products/wsntlg-timber-screw-flooring-screw-collated>

8.

Company Contact Details

Importing Branch: Simpson Strong-Tie New Zealand
Address: 52A Arrenway Drive
Albany, Auckland 0632 New Zealand
Phone: +64 9 477 4440
Website: www.strongtie.co.nz

Manufacturing Branch: SST Branch 8200 Taiwan
Address: Zhongshan 2nd Road
Qianzhen District
Kaohsiung City 806
Website: www.simpsonmfg.com
Phone: Please call NZ Head Office.

9.

Warnings and Bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

10.

Safety:

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

11.

Appendix – BPIR Ready Selections

B1 Structure

B1.3.1

Buildings, building elements and site work shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

11.

Appendix – BPIR Ready Selections

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings*; *building elements* and *site work*, including:

- (b) Imposed gravity loads arising from use
- (d) earth pressure
- (e) water and other liquids
- (f) earthquake
- (g) snow
- (h) wind
- (j) impact
- (q) time dependent effects including creep and shrinkage

B1.3.4

Due allowances shall be made for:

- the consequences of failure,
- the intended use of the *building*,
- effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- variation in the properties of materials and the characteristics of the site, and
- accuracy limitations inherent in the methods used to predict the stability of *buildings*

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (a) The life of the building, being not less than 50 years, if:
 - those *building elements* (including floors, walls, and fixings) provide structural stability to the *building*, or
 - those *building elements* are difficult to access or replace, or
 - failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the building