

DHW — Decking Screw Hardwood-to-Softwood (Collated & Loose)

Material

305 Stainless Steel



Size: See the table below

Features & Benefits

- Compact Head for countersunk finish and discreet appearance
- Designed to penetrate the hardest timber without predrilling
- Wings on the shaft counter-bore hard timber to allow the head to countersink for clean look
- Stainless Steel has the ductility to allow for movement of timber decking

Applications

- Hardwood Decking and exterior Hardwood-to-Softwood joist
- This screw is available for both hand-drive and collated Quik Drive® system



Specifications - Hand-drive

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SSDHW60R250	10G x 60mm	Coarse Threads	Hardwood Drill Point	305 Stainless Steel	250	#2 Square Drive	BIT2S-2-RC3
SSDHW60R1100					1100		



Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SSDHW60SA	10G x 60mm	Coarse Threads	Hardwood Drill Point	305 Stainless Steel	1000	#2 Square Drive	BIT2S-RC10

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.



Compact Head
countersinks easily.



Winged Design easily bores out hardwood to allow head to countersink perfectly.



Hardwood Drill Point
requires no predrilling.

Deck-Drive™

Quik Drive®