

# SD — Strong-Drive® Connector Screw

**Material:** Carbon Steel

**Finish:** Mechanically Galvanised



**Size:** See the table below

**Features & Benefits**

- Specifically designed to replace nails in certain Simpson Strong-Tie® connectors, and is the only screw approved for that application
- 1/4" Hex Head reduces cam-out for easier installation
- Shank is specifically designed to match the fastener holes in Simpson Strong-Tie connectors
- Serrated Threads and Sharp Point make driving easier
- Optimised heat treating for ductility and strength

**Applications**

- Simpson Strong-Tie® Connectors



**Head Stamp** for easy screw identification



**Ductility and Strength** through optimised heat treating



**Patented Serrated Threads and Sharp Point** make driving easier



**Strong-Drive®**

**Specifications - Hand-drive**

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size
SD9112R100	#9 x 38mm	Serrated Threads	Sharp Point	Mechanically Galvanised	100	1/4" Hex Head
SD9212R100-R	#9 x 64mm				100	
SD9212R500					500	
SD9212MB					2000	
SD10112R100					#10 x 38mm	
SD10112R500	500					
SD10212R100-R	#10 x 64mm					

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.