

SS3DSC – Timber Screw Flooring - Collated

Material

305 Stainless Steel



316 Stainless Steel



Size: See the table below

Features & Benefits


- Coarse Thread
- Type-17 Point ideal for timber applications
- Bugle Head for clean, flush, countersunk finish
- Option of 305 or 316 Stainless Steel

Applications


- Timber Flooring



Bugle Head for clean, flush, countersunk finish



Type-17 Point enable easy driving with no predrilling and minimal splitting



Option of **305** or **316** Stainless Steel



Quik Drive®

Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SS3DSC212BS	10G x 65mm	Coarse Threads	Type-17	305 Stainless Steel	1500	#3 Square Drive	BIT3S-RC10
SS3DSC3BS	10G x 75mm				1000		
SS3DSC212BS316	10G x 65mm			316 Stainless Steel	1500		
SS3DSC3BS316	10G x 75mm				1000		

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.