

SSDTH — Timber Screw Weatherboard Screw (Collated)

Material

305 Stainless Steel



Size: See the table below

Features & Benefits

- No pre-drilling required.
- Consistent countersink means no punching required
- Trim Head for clean and less noticeable finish
- Unique Box Threads design with raised-ridge technology greatly reduces driving torque
- Easy to reverse out means no broken boards if you need to remove the fastener
- BRANZ Appraised for performance you can trust
- Suitable for NZS 3604 extra high wind zones

Applications

- Weatherboard Cladding
- Timber Cladding
- Timber-to-Timber
- Wall Cladding

Approvals

- BRANZ Appraisal No. 1044



Trim Head ideal for a less noticeable fixing



Box Threads greatly reduces driving torque



Sharp Point with Nib penetrates softwood timber products with ease



Quik Drive®

Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SSDTH2SA	7G x 50mm	Box Threads	Sharp Point with Nib	305 Stainless Steel	2000	#2 Square Drive	BIT2S-RC10
SSDTH221S	7G x 65mm				1000		
SSDTH3S	7G x 75mm				1000		

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.