

WSC – Timber Screw Flooring Screw (Collated)

Material

305 Stainless Steel: SSWSC

Carbon Steel, Yellow Zinc: WSC

Size: See the table below




Features & Benefits


- Flat Head with Nibs for easy countersinking
- Coarse Threads
- Type-17 Point ideal for timber applications

Applications


- Timber-to-Timber
- Timber Flooring
- Roofing (plywood fixing) - SSWSC



Flat Head with Nibs
for easy countersinking



Coarse Thread ideal for timber applications



Type-17 Point ideal for timber applications



Quik Drive®

Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
SSWSC134BS	8G x 45mm	Coarse Threads	Type-17	305 Stainless Steel	2000	#2 Square Drive	BIT3S-RC10
SSWSC2BSA10	10G x 50mm					#3 Square Drive	
WSC114SA	8G x 32mm			Carbon Steel Yellow Zinc	2500	#2 Square Drive	BIT2S-RC10

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.