

WSNTLG — Timber Screw Flooring Screw (Collated)

Material

Carbon Steel

Finish

Class 3 Mechanically Galvanised




Size: See the table below

Features & Benefits


- Flat Head with Nibs for easy countersinking
- Twin Threads for better clamping force
- Sharp Point for fast starts saving time on the worksite
- #3 square drive

Applications

- Exterior Timber-to-Timber



Flat Head with Nibs for easy countersinking



Twin Threads for better clamping force



Sharp Point for easy starts into timber



Quik Drive®

Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
WSNTLG2SA	8G x 50mm	Twin Threads	Sharp Point	Carbon Steel Class 3 Mechanically Galvanised	2000	#3 Undersize Square Drive	BIT3SU-RC10

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.